

---

<b>Product name</b>	:	<b>MoTip Anti-Welding Spray</b>	
<b>Article number</b>	:	<b>090404</b>	
<b>Supplier / Producer</b>	:	<b>MOTIP DUPLI B.V.</b>	
		<b>Wolfraamweg 2</b>	
		<b>NL-8471 XC WOLVEGA</b>	
		<b>Telephone number</b>	<b>+31 561 – 69 44 00</b>
		<b>Telefax number</b>	<b>+31 561 – 69 44 31</b>

---

### Product description

High quality spray to prevent adhesion of welding spatter on the welding mouth and the surroundings of the welding zone.

### Applications

Welding guns  
Welding zones

### Product characteristics

Non-flammable  
Can be removed with water  
Silicone-free  
Non-corrosive  
Slightly basic  
Misty spray pattern  
360° valve

### Physical and Chemical Characteristics

Contents	:	400 ml
Basis	:	Emulsifying Oil
Propellant	:	Inert propellant
VOC-content	:	0% w/w
Colour	:	Transparent white
Relative density at 20°C	:	1,0 g/ml
Yield	:	2,7 gr/sec.
Vapour pressure at 20°C	:	8 to 9 bar
Rest pressure	:	Approximately 3,0 bar
pH-value	:	8,5 – 9,5



### Usage

**Before use, carefully read the directions on the packaging and act accordingly.**  
**Store frost-free.**

Best processing temperature 5 to 35°C.  
Before use, shake the aerosol.

Spray the parts to be protected and execute the welding.  
Remove welding spatter with a steel brush.  
If desired, remove oil with water or a moist cloth.